

JUNO 65

IP65 EMERGENCY NM TWIN SPOT

JUNO 65 is the ideal solution for adjustable, nonmaintained emergency lighting in any wet or dusty environment. The high light output suits higher mounting applications and where flexibility is a prime consideration



Features

- Tough IP65 & IK08 construction, ideal for wet or dusty environments
- Fully adjustable LED projector flood heads
- High output, suited to higher mounting positions
- Fast and easy to install

Specification

Code	Description	Lumen Output	Emergency Lumen Output	Wattage	Efficacy
JUN65/500/ST	Juno 65 NM Emergency Twin Spot Self Test 3 Hr 500lm IP65	500 lm	500 lm	4W	125 lm/W

Product Information

Guarantee	5 Years
Emergency Battery Guarantee	5 Years
On-Site Warranty	2 Years
Colour Appearance (CCT)	6500K
IP Rating	IP65
IK Rating	IK08
Emergency Battery Type	LiFePO4
Voltage	220-240V
Material (Body/Housing)	Polycarbonate
Material (Diffuser/Cover)	Polycarbonate

Colour Rendition (CRI)	>80
Colour Finish	White RAL9003
LED Life Expectancy	36000hours
Power Factor	>0.3
Frequency	50/60Hz
Driver Type	Fixed
Approval	UKCA CE
Electrical Class	Class II
Working Temperature	0°C to +45°C
EM Working Temperature	0°C to +45°C

JUNO 65

IP65 EMERGENCY NM TWIN SPOT

Packaging Information

Dimensions (mm)	L: 300 x W: 288 x D: 69 mm
Product Net Weight (kg)	1.139 kg
Barcode	5055807624442
Box Dimensions (mm)	L: 314 x W: 292 x D: 73 mm
Box Gross Weight (kg)	1.32 kg

Units/Outer Carton	10
Outer Carton Barcode	15055807624449
Outer Carton Dimensions (mm)	L: 605 x W: 330 x D: 390 mm
Outer Carton Gross Weight (kg)	14.2 kg

